



### Features:

- Clean burn, cast iron stove
- Will heat up to 100m<sup>2</sup>
- Stay clean side glasses that provide good view of flames
- Ash pan facility
- Easy to use air vent
- 10 year limited warranty

## Specifications:

Heating capacity: 100m<sup>2</sup> Approx weight: 115Kg Flue diameter: 150mm (6 inch) Flue exit options: top or rear Max usuable log length: 33cm Average peak output: 10kW Overall efficiency: 85%



# Jøtul F163

Jøtul F 163 is one of the most efficient heaters on the market. This is a small wood stove with a new and unique look, characterised by its large side glasses and three sturdy legs. The shape and size makes it suitable for both corner and standard installations. Designed to suit modern living and powerful enough to heat up 100m<sup>2</sup>. Available in either black paint, white or black enamel.

## Clearances

MODEL	FLUE KIT	REAR CLEARANCE	SIDE CLEARANCE	CORNER CLEARANCE	HEARTH FORWARD OF DOOR OPENING	HEARTH FROM SIDE OF HEATER		MIN HEARTH SIZE
With 1200mm high 160 degree flue shield	Australian standard kit with decromesh	250mm	750mm	525mm	350mm	225mm	15mm thick cement sheet	900mm x 900mm

Pecan Engineering Pty Ltd 13 Acorn Road, Dry Creek South Australia 5094 AUSTRALIA

Telephone 08 8349 8332 Fax 08 8260 6643 www.jotul.com www.jotul.com.au